

VISIT...

LANZAROTE
Caliente.COM

AQUAPANEL®

Exterior Primer

Synthetic dispersion with high alkali resistance



AQUAPANEL® Exterior Primer is used as an undercoat for AQUAPANEL® Exterior Basecoat as well as a primer over basecoated substrates where AQUAPANEL® exterior finishes, e.g. AQUAPANEL® Exterior Silicon Synthetic Resin Plaster - White or AQUAPANEL® Dispersion Plaster - White are used on AQUAPANEL® Cement Board Outdoor. It reduces suction variations.

Material characteristics

- High resistance to alkalis
- Dries to white

Background/pre-treatment

The background must be rigid, dry, clean and free of loose parts and peeling residues. The background and air temperature must not be below +5°C during use.

Processing

AQUAPANEL® Exterior Primer is applied undiluted across the entire surface with a lamb's wool roller or brush. Stir bucket contents occasionally. Leave at least 24 hours between priming and finishing plaster. The primer must be completely dry.

Clean tools and equipment with water immediately after use.

Coverage

Approx. 100 – 150 g/m²

Working time

Approx. 1 minute/m²

Working temperature/climate

The background and air temperature must not be below +5° during use.

Method of delivery/storage

- 15 kg/pail
- Can be stored for approx. 12 months in a frost-free area

Item code: 49299